

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- SALIDA faceplate available.
- Single or double face(Universal)
- Universal J-box mounting pattern.
- 120V-277VAC Dual voltage operation.
- Ultra bright RED or GREEN LEDs.
- Built-in 1.2V1000mAh Ni-MH battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

ORDERING INFORMATION

FAMILY	LENS	HOUSING COLOR
JLEED2	R(RED)	BLANK(WHITE)
	G(GREEN)	B(BLACK)
TYPE	LETTER	
	BLANK(AC ONLY)	BLANK(EXIT)
	E(BATTERY BACKUP)	

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLEED2RWEM	43x32.7x19cm/8pcs	6.5/5.5kgs
JLEED2GWEM	43x32.7x19cm/8pcs	6.5/5.5kgs
JLEED2RW AC ONLY	43x32.7x19cm/8pcs	6.5/5.5kgs
JLEED2GW AC ONLY	43x32.7x19cm/8pcs	6.5/5.5kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLEED2RWEM	120 - 277V	0.023A	1.6W	10Pcs Red LEDs	24 Hrs	90 Mins
JLEED2GWEM	120 - 277V	0.023A	1.6W	8Pcs Green LEDs	24 Hrs	90 Mins
JLEED2RW	120 - 277V	0.02A	1.2W	10Pcs Red LEDs		
JLEED2GW	120 - 277V	0.02A	1.2W	8Pcs Green LEDs		

FAMILY: **JLEED2**

NOTES:

TYPE: **ULTRA THIN EMERGENCY EXIT SIGN**

CEC DOE FC

